



BORMA WACHS®

DECKING OIL HD

Quality of the classics:
the beauty of the
oil protection

High quality blend of natural oils
reinforced with resins for the
finishing of exterior surfaces. Fast,
resistant and strongly decorative



Exteriors



Oils



UV FILTERS

DECKINGOILHD



Plus:

- Special formulation that combines the natural properties of oils and the strength of resins
- Suitable for any exterior wooden surface: terraces, claddings, furniture, windows
- Recommended as transparent topcoat, it can be used alone in two or three coats
- To increase protection and decoration it can be over-applied on Teak Oil, or wax oil Holzschutz lasur.
- Enriched with UV filters and certified additives against harmful agents
- Fast drying
- Bodied effect



Customizable with Borma Color System



Exteriors



Oils



- Remove grease and residuals of old lacquers



- The product is ready for use



10/20%

- In case of difficult or exotic woods, to improve wetting properties, dilute 10- 20% with Solvoil 06, unless for the first coat



- Apply the first coat by brush or roller



8/12h

- Let dry for 8-12 hours



- For soft touch, lightly sand the treated surface (grit 220-240)



- Remove dust and apply second coat.



- Whether aimed a third coat can be applied as well.



- Maintenance: for better look, light sanding and apply a new coat

- For regular or intensive cleaning use the proper waterborne detergents from Borma range

Learn more about BORMAWACHS:



www.bormawachs.com

