



**BORMA WACHS**<sup>®</sup>  
Wood Professional Cosmetics & Eco-Finishes



Exteriors



Interiors

# ONE COAT 2K WOOD OIL

Blend of natural oils,  
VOC free.

High performance VOC free blend of natural oils for the protection of any wooden surface, interior and exterior, in one single coat.  
The universal solution.





Exteriors



Interiors

## ONE COAT

Code 4996 + 4996K - 6 x 1Lt + 1 x 300ml, Code 4997 + 4997K - 2 x 2,5Lt + 1 x 750ml

Code 4998 + 4998K - 2 x 5Lt + 1 x 1,5Lt, Code 4999 + 4999K - 1 x 20Lt + 1 x 6Lt



### Plus:


- High performances in one single coat
- Natural, satin effect
- No emissions, based on vegetable oils
- High protection on any kind of wood, even exotic
- Perfect for all indoor and outdoor surfaces, it is suitable for parquet, table tops, bathrooms, kitchens, terraces and external claddings, as well as garden furniture.
- Enriched with UV filters and additives for the protection of wood
- Easy application, buffing machine not compulsory



- Sand the surface to be treated grit 100-120 and remove grease and dust



- For higher protection and durability of exterior surfaces, apply a first coat of Naturaqua Holz Lasur or Naturaqua Borma Shield, better if pigmented.



100:30

- Mix the product with its catalyst (catalysis ratio 100:30)



10%

- Dilute with 10% of Solvoil Plus to improve workability.



- On interior floors: Spread the product uniformly all over the surface.



- Reprocess with a buffing machine (white pad) to remove the excess, help the drying and obtain a uniform effect.



10%

- On garden furniture and terraces: dilute with an additional 10% of Solvoil Plus and mix well.



Apply by brush or roller. After 10/20 minutes of absorption, remove the excess with a cloth or an abrasive cloth, passing over the surface to obtain a uniform effect.



24/36h

- Total drying time 24-36 hours.



Learn more about BORMAWACHS:



[www.bormawachs.com](http://www.bormawachs.com)