



BORMA WACHS[®]
Wood Professional Cosmetics
& Eco-Finishes



Exteriors

NATURAQUA HOLZ LASUR SHIELD PROTECTOR

NF01A

Wood primer against woodworm



Biocidal product PT8 WOOD PRESERVATIVES,
registered and approved according to (EU)
Biocidal Products Regulation n. 528/2012.
Authorization n. IT/2019/00559/MRS.





BORMA WACHS®

Wood Professional Cosmetics
& Eco-Finishes

NF01A

Wood staining primer against woodworm

NF01A is a waterbased preservative ready-to-use primer for wood, that penetrates deeply and improves the adhesion of the top coat. The product is a blend of micro-emulsified preservatives, that are highly effective in protecting wood against blue stain fungi, soft rot fungi, woodworm (*Hylotrupes bajulus*) and termites. It is to be applied once as a preventive treatment in the quantity of 200 ml of product per 1 sqm of wood. After it has dried, it is necessary to apply a finishing varnish.



Fields of application:

The protection of all kinds of wood outside, wooden carpentry structures and constructions, beams and cladding, doors and windows, as well as other wooden artifacts not in contact with the ground. The product must be used outdoors by professionals and non-professionals in classes of use 2 and 3 (wood above ground exposed to the elements, not in continuous contact or not immersed in water).

Properties:

- Effectively protects the wood from the attacks by fungi and decay
- Suitable for outdoor use.
- Maximum penetration.
- Uniforms surface's absorption

Advantages:

- Grants a long-lasting protection
- Prolongs the service life of wood.
- Reduces the consumption of following layers
- Easy application
- Increases the adhesion of the top coat
- Ensures an easy application of the next coat

The active ingredients and the biocidal product NF01A are registered and approved according to (UE) Biocidal products regulation n. 528/2012.

Active ingredients:

3-iodo-2-propynyl butylcarbamate	CAS 55406-53-6	0,75% p/p
propiconazole	CAS 60207-90-1	0,24% p/p
α-cypermethrin	CAS 52315-07-8	0,15% p/p

Tested according to the UNI EN 46, UNI EN 118, UNI EN 152, UNI EN 113 standards.
To be used only in use classes 2 and 3 cfr. DS/EN335:2013, not suitable for wood that is in continuous contact or immersed in the ground and/or water.



Exteriors



Application by brush and roller.

The product is ready to use and must not be diluted.

Mix thoroughly before use.

Application quantity: 200 ml of product per sqm of wood. Drying time: stackable and overcoatable in approximately 24 hours.

Application and drying temperature must be above 5°C and the relative humidity below 80%.

WARNING

Treated wood requires the application of finishing treatment.

It is recommended to carry out maintenance for the surface paint treatment.

Only to be used in usage classes 2 and 3 cf. DS/EN335:2013.

Not suitable for wood in continuous contact or immersed in soil and/or water.

Do not use indoors, except for exterior window frames and exterior doors.

To be used only as a wood preservative.

Cover the ground when applying outdoors.

Do not apply in areas where the product may reach surface water during application, such as a bridge over a pond.

Do not use the treated wood near aquatic ecosystems

Cartella colori:



08 Cler



05 Pine



03 Oak



17 Teak/Chestnut



10 Larch



54 Douglas




16 Cherry



62 Mahogany



53 Light Walnut



59 Medium Walnut



63 Dark Walnut



136 Pine Green



More about BORMAWACHS:

www.bormawachs.com

